

E 70 | 80 | 90 | 100



- 3 AND 4 CYLINDER RANGE, UP TO 102 HP
- MAXIMUM ADHERENCE TO THE GROUND
- 16+16 TRANSMISSION WITH SYNCHRONISED REVERSE SHUTTLE
- WEIGHT 2325 KG

Four x 1, one for all

Securely positioned on four low, wide drive wheels which receive equal power, the E Series range of isodiametric tractors is the perfect solution for safe operations even in the most challenging situations, thanks to the new, tapered chassis and the extremely narrow turn radius.

As of today, these models are now available in the new 4-cylinder version, with up to 100 HP: never before has a tractor been so powerful, so reliable or so Goldoni.

TECHNICAL FEATURES

ENGINE

VM 3 Cyl 45 kW 61 HP- 52 kW 71 HP

VM 4 Cyl 60 kW 81 HP - 68 kW 92 HP

Tier IIIB

DPF + IGR

TRANSMISSION

16+16, 12+12, 8+8

Mechanical Reverse Shuttle

Electro-hydraulic DIFF-lock

HYDRAULIC

Lifting capacity 2200 kg

Pump output 55 l/min, open-centre
with up to 4 rear mechanical distributors (3+1)

DRIVER AREA

Plat

DIMENSIONS

Wheelbase: 1505 mm

Weight: 2275-2325 kg

Tyre: 320/70R20

Width (min-max): 1335-1575 mm