

E SN 20

20 Articulated



- ROBUST
- ARTICULATED
- MINIMUM WIDTH 80 CM
- THE MOST COMPACT EQUAL SIZE WHEEL IN THE WORLD

Compact and simple

The E 20 SN is the ideal tractor both for the most exacting professionals and for hobby users who need a robust, compact machine that is also economical to run. Small, practical and highly functional, the E 20 SN is an articulated tractor with isodiametric wheels that offers an effective response to operators who require high levels of manoeuvrability and functionality in a small machine.

TECHNICAL FEATURES

ENGINE
2 Cyl 16 kW 22 HP
Tier IIIA
Direct injection
TRANSMISSION
6+3
Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 500 kg
Pump output 11 l/min, open-centre with rear mechanical distributor
DRIVER AREA
Plat
DIMENSIONS
Wheelbase: 1000 mm
Weight: 750 kg
Tyre: 6.00R16
Width (min-max): 800-810 mm

E RS-SN 30/40/50

30RS 4WD
40RS 4WD
50RS 4WD
50SN centre-articulated



- EXCELLENT PRICE/PERFORMANCE RATIO
- THE "ENTRY LEVEL" TRACTOR
- FOUR WHEEL DRIVE AND ARTICULATED
- LOW, SPACIOUS AND ERGONOMIC DRIVING POSITION

Power, simplicity and performance

With the E series range of four-wheel drive isodiametric tractors, Goldoni provides an effective response to the handling, agility and stability requirements of operators working on sloping terrain with limited space to manoeuvre. The E range includes tractors with 25 to 38 HP in either four wheel drive (RS) or articulated (SN) versions, for applications in which an even narrower turn radius is necessary.

TECHNICAL FEATURES

ENGINE
2/3 Cyl Euro 30: 19 kW 25 HP
E 40: 25 kW 33 HP
E 50 28 kW 38 HP
Tier IIIA
Direct injection
TRANSMISSION
6+3
Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 1000 -1200 kg
Pump output 18.5 -25 l/min, open-centre with rear mechanical distributor
DRIVER AREA
Plat
DIMENSIONS
Wheelbase: 1155 mm
Weight: 1100 kg
Tyre: 8.25R16
Width (min-max): 1098-1360 mm

E RS-SN 60

60RS 4WD
60SN centre-articulated



- COMPACT WHEELBASE
- MAXIMUM ADHERENCE TO THE GROUND
- 16+16 TRANSMISSION WITH SYNCHRONISED REVERSE SHUTTLE
- 1650 KG

The evolution of isodiametric tractors

The combination of a tapered chassis, a reduced steering radius, four-wheel drive and the powerful 48 HP direct injection engine make the E the ideal machine for working between narrow rows in vineyards and low-hanging orchards with limited room to manoeuvre. The compact load-bearing structure of this model ensures the centre of gravity remains low and close to centre of the machine, enabling optimal weight distribution for safe operation, even when using very

TECHNICAL FEATURES

ENGINE
VM 3 Cyl 35 kW 48 HP
Tier IIIA
Direct injection
TRANSMISSION
12+4, 16+16
Mechanical Reverse Shuttle
Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 1500 kg
Pump output 38 l/min, open-centre with up to 2 rear mechanical distributors
DRIVER AREA
Plat
DIMENSIONS
Wheelbase: 1370 mm
Weight: 1650 kg
Tyre: 300/70R20
Width (min-max): 1195-1515 mm

E 70|80|90|100



- 3 AND 4 CYLINDER RANGE, UP TO 102 HP
- MAXIMUM ADHERENCE TO THE GROUND
- 16+16 TRANSMISSION WITH SYNCHRONISED REVERSE SHUTTLE
- WEIGHT 2325 KG

Four x 1, one for all

Securely positioned on four low, wide drive wheels which receive equal power, the E Series range of isodiametric tractors is the perfect solution for safe operations even in the most challenging situations, thanks to the new, tapered chassis and the extremely narrow turn radius. As of today, these models are now available in the new 4-cylinder version, with up to 100 HP: never before has a tractor been so powerful, so reliable or so Goldoni.

TECHNICAL FEATURES

ENGINE
VM 3 Cyl 45 kW 61 HP- 52 kW 71 HP
VM 4 Cyl 60 kW 81 HP - 68 kW 92 HP
Tier IIIB
DPF + IGR
TRANSMISSION
16+16,
Mechanical Reverse Shuttle
Electro-hydraulic DIFF-lock
HYDRAULIC
Lifting capacity 2200 kg
Pump output 55 l/min, open-centre with up to 4 rear mechanical distributors (3+1)
DRIVER AREA
Plat
DIMENSIONS
Wheelbase: 1505 mm
Weight: 2275-2325 kg
Tyre: 320/70R20
Width (min-max): 1335-1575 mm



a Keestrack brand



PRODUCT
CATALOGUE

EN



a Keestrack brand

RONIN 50



- 48 HP
- 12+12 TRANSMISSION + FAST REVERSE (FURTHER 4WD SPEEDS)
- ITALIAN DESIGN
- MULTIFUNCTIONAL

TECHNICAL FEATURES

ENGINE
Lombardini 4 Cyl - Ronin 50: 35.3 kW 48 HP
Tier IIIA
Direct injection
TRANSMISSION
12+12+4 Fast reverse
Synchronised mechanical reverse shuttle 4WD and Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 1800 kg
pump output 33 l/min, open-centre
3 rear mechanical distributors
DRIVER AREA
Integrated platform/cab on silent-block suspension
DIMENSIONS
Wheelbase: 1723 mm
Weight: (Plat): 1475 kg
Tyre: 320/70R24
Width (min-max): 1309-1500 mm

S 60|80

- THE SHORTEST WHEELBASE IN ITS CATEGORY
- EXCLUSIVE PATENTED TRANSMISSION
- NARROW STEERING RADIUS
- MAXIMUM STABILITY AND ADHERENCE TO THE GROUND THANKS TO OPTIMAL WEIGHT DISTRIBUTION
- THE MOST ROBUST 50 HP MODEL ON THE MARKET



The complete range for orchards and vineyards

The Goldoni S Series meets all of the needs and requirements of professionals operating in vineyards and orchards: power, manoeuvrability, reliability and performance combine to make these tractors the ideal partner for working in the often challenging conditions that characterise specialised crop applications. One of the key advantages of the S Series is its compact dimensions.

TECHNICAL FEATURES

ENGINE
VM 3 Cyl - 35 kW / 48 HP / 4 Cyl 55 kW 75 HP
3 Cyl Tier IIIA / 4 Cyl Tier IIIB Turbo
Direct injection
TRANSMISSION
Dual Power 16+8, 8+8 transmission with lateral levers
Mechanical Reverse Shuttle 4WD and Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 2300 kg
pump output 38 l/min, open-centre
3 rear mechanical distributors
DRIVER AREA
Semi-platform
Integrated platform/cab on silent-block suspension
DIMENSIONS
Wheelbase: 1690-1831 mm
Weight: 1900 kg
Tyre: 360/70R20
Width (min-max): 1318-1794 mm

S 80 PLUS



- COMPACT WHEELBASE
- EXCLUSIVE PATENTED TRANSMISSION WITH THE "DUAL POWER" SYSTEM
- DRIVING COMFORT: PLATFORM ON "SILENT BLOCK" AND "OVERVIEW" CAB WITH A/C
- EXCELLENT WEIGHT/POWER RATIO AND WEIGHT DISTRIBUTION
- TYPE-APPROVED TO 40 KM/H

Even more advanced

Starting with this Series, we have worked to further develop its strengths, adding a host of more advanced, comprehensive features: S 80 that boast all the power you need, combined with the unrivalled agility and reliability that characterise all Goldoni products. It is the perfect choice for those working in the specialised crop sector who don't want to compromise on cutting-edge equipment and performance.

TECHNICAL FEATURES

ENGINE
VM 4 Cyl 55 kW 75 HP
Tier IIIB Turbo
Direct injection
TRANSMISSION
Dual Power 16+8, 8+8 transmission with lateral levers
Mechanical Reverse Shuttle 4WD and Mechanical DIFF-lock
HYDRAULIC
Lifting capacity 2300 kg
pump output 38 l/min, open-centre
3 rear mechanical distributors
DRIVER AREA
Integrated platform/cab on silent-block suspension
DIMENSIONS
Wheelbase: 1831 mm
Weight: 1900 kg (platform)
Tyre: 360/70R20
Width (min-max): 1290-1766 mm

S 90|100|110

S 90|100|110 GT

- HYDRAULIC CIRCUIT FLOW RATE 39+61 LITRES
- OPTIMAL WEIGHT DISTRIBUTION
- MAXIMUM VERSATILITY: S - EASY TO HANDLE AND AGILE S GT - ROBUST AND COMPACT
- DRIVING COMFORT: PLATFORM ON "SILENT BLOCK" AND "PRESSURISED" CAB WITH A/C



May the force be with you

A "compact" tractor for orchards and vineyards that boasts more than 100 horsepower? Operators who choose the S Series (with turbo intercooler, four wheel drive, platform on silent-block suspension or cab with panoramic view and air conditioning) will not miss having a bigger machine. Perfectly balanced, compact and tough, it offers tireless performance, and is the ideal companion for stress-free operation: available in 6 versions, so you can choose EXACTLY the right model for you.

TECHNICAL FEATURES

ENGINE
VM 4 Cyl Tier IIIB
S 90: 59 kW / 80 HP
S 100: 67 kW / 91 HP
S 110: 75 kW / 102 HP
DPF + IGR
TRANSMISSION
24+12 transmission with 4 gears across 3 ranges + underdrive (20%)
Mechanical Reverse Shuttle 4WD and electro-hydraulic DIFF-lock
HYDRAULIC
Lifting capacity 2500 kg
Electronically controlled lift (optional)
Pump output 100 l/min (39+61), open-centre up to 3 rear mechanical distributors up to 3 front electro-hydraulic distributors
DRIVER AREA
Pressurised platform / cab
DIMENSIONS
Wheelbase: 1973 mm / 1990 GT version
Weight: 2375 kg (Plat)
Tyre: 360/70R24 / 360/70R28 GT version
Width (min-max): 1404-1830 mm

Q 90|100|110



- LOW CENTRE OF GRAVITY FOR MAXIMUM TRACTION AND ADHERENCE TO THE GROUND
- VERSIONS WITH SUPER "LOW PROFILE" CAB (JUST 174 CM HIGH)
- DRIVING COMFORT: PLATFORM ON "SILENT BLOCK" WITH VARIABLE VISCOSITY
- MORE VERSATILE THAN AN ISODIAMETRIC TRACTOR, WITH BETTER PERFORMANCE THAN A CRAWLER AND SUPERB ROAD HANDLING
- PERFECT WEIGHT DISTRIBUTION

A class apart

When it comes to tractors, Q really is a class apart, and is unmatched by any other solution on the market. The aggressive, sloping design of the chassis, the reduced steering radius, the four large drive wheels (which are almost isodiametric) and the powerful engine make the Q the ideal machine for working in orchards and vineyards where limited heights and reduced room to manoeuvre can be challenging, as well as on steep and sloping terrain in general. The compact load-bearing structure, with 50% of the weight distributed on the front axle and 50% on the rear, keeps the centre of gravity low and near the centre of the machine. It also enables maximum traction to be transferred to the ground for safe operation even when working with heavy implements on extreme slopes.

TECHNICAL FEATURES

ENGINE
VM 4 Cyl Tier IIIB
Q 90: 59 kW / 80 HP
Q 100: 67 kW / 91 HP
Q 110: 75 kW / 102 HP
DPF + IGR
TRANSMISSION
24+12 transmission with 4 gears across 3 ranges + underdrive (20%)
Mechanical Reverse Shuttle 4WD and electro-hydraulic DIFF-lock
HYDRAULIC
Lifting capacity 2500 kg
Electronically controlled lift (optional)
Pump output 100 l/min (39+61), open-centre up to 3 rear mechanical distributors up to 3 front electro-hydraulic distributors
DRIVER AREA
Pressurised platform / cab
DIMENSIONS
Wheelbase: 1923 mm
Weight: 2275 kg (Plat)
Tyre: 420/65R20
Width (min-max): 1591-1876 mm

TRANSCAR 40-80 RS-SN



- FOUR WHEEL DRIVE WITH FRONT TRACTION
- DRIVING COMFORT: PLATFORM ON "SILENT BLOCK"
- 4 INTEGRATED BRAKES, 290 DIAMETER
- FRONT AND REAR HYDRAULIC CONTROL DIFFERENTIAL LOCKING
- THE LEADING TRACTOR WITH LOADING PLATFORM ON THE MARKET

The most widely-sold and comprehensive range of platform tractors and machinery in Italy

The Goldoni Transcar range is designed to meet the specific needs of operators working in mountainous terrain who need a machine that can handle and move materials. With a wide range of engines from 38 to 71 horsepower, air or water cooling and a choice between four wheel drive or articulated machines, two versions of this tractor are available, type-approved either as an agricultural tractor or as an

TECHNICAL FEATURES

ENGINE
3 Cyl. - from 38 HP to 71 HP
Tier IIIA/ Tier IIIB Turbo intercooler (Transcar 80)
TRANSMISSION
8+8
Mechanical Reverse Shuttle 4WD and electro-hydraulic DIFF-lock
DRIVER AREA
Integrated semi-platform/platform on silent-block
DIMENSIONS
Transcar 40-80: 2280- 2580
Weight: 1940 kg
Tyre: 10.0/75-15.3