



**G GOLDONI**



**C60**

**MACHINES  
FOR LIFE —**

## Specifications

DESCRIPTION	VALUE
<b>ENGINE</b>	
Brand	Doosan
Rated power (ECE R120)	40Kw/55HP
Emissions type	STAGE V
Number of cylinders	3
Maximum torque	160Nm (@1400-2000 rpm)
Torque backup	0,35
Fuel Tank capacity	45 liters
Fuel Tank capacity	45 liters
<b>TRANSMISSION</b>	
Gearbox type	12+12+4 Fast Reverse
Rear differential lock	Mechanic
Front axle	4WD
Front wheel drive engagement control	Electrohydraulic
Minimum speed	0.6 km/h
Maximum speed (homologated)	30 Km/h
<b>BRAKES</b>	
Rear braking type	Oil-bath multidiscs, Mechanical control
<b>STEERING</b>	
Steering type	Hydrostatic
Steering angle	55°
<b>REAR POWER TAKE-OFF</b>	
Type	Single shaft, independent and synchronized
Independent speeds	540/1000 rpm
Ground speed synchronized	Yes
Independent speeds	540/1000 rpm
Ground speed synchronized	Yes
<b>FRONT POWER TAKE-OFF</b>	
Type	Independent singleshaft
Independent speeds	540/1000 rpm
Independent speeds	540/1000 rpm
<b>REAR LIFT</b>	
Type	Hydraulic Raise and down
Lifting capacity at the ballend	1800 Kg
Right-hand tie rod type	Mechanic
<b>FRONT LIFT</b>	
Type	Hydraulic Raise and down
Lifting capacity at the ballend	500 Kg
<b>HYDRAULIC CIRCUIT</b>	
Type	Open center

DESCRIPTION	VALUE
Pump flow rate	50 liters/minute
Rear hydraulic spool valves	No.2 in single-acting double-acting with spring-loaded lever return
Front hydraulic spool valves	One-piece 3-way front hydraulic spool valve
<b>ELECTRICAL SYSTEM</b>	
Dashboard	ECO-HE digital display
Cruise Control	2 RPM Cruise control
G FARM	G FARM Ready ( digital agriculture platform)
7-pin socket	12 Volt
<b>OPERATOR AREA</b>	
Platform	Integral suspended
Seat adjustments	Horizontal, vertical, driver weight
<b>CABIN</b>	
Ventilation and heating system	Electroventilated
Air conditioning system	Electroventilated condenser on cabin roof
<b>TOWING DEVICES</b>	
Rear tow hook	Category X/Y
<b>BALLASTS</b>	
Front	75Kg in 5 cases of 15Kg
<b>DIMENSIONS AND WEIGHTS</b>	
Wheelbase	1723 mm
Width (min-max)	1090 - 1500 mm
Height with Standard cab (min-max)	2090-2180 mm
Height to hood mask (min-max)	1033 - 1039 mm
Height at the steering wheel (min-max)	1348 - 1374 mm
Height to seat (min-max)	1075 - 1187 mm
Height to rear fender (min-max)	1208 - 1240 mm
Ground clearance (min-max)	296 - 316 mm
Minimum turning radius (inside)	2,3 m
Weight with ROPS	1600 Kg
Weight with standard cabin	1810 Kg
Length (front bumper/rear lift arms)	2949 mm
Distance between wheels interior (min-max)	650 - 751 mm
<b>TYRES AND DIMENSIONS ROLL BAR VERSION</b>	
Wheel set Rear 360/70R20 Front 11.0/65R12	Minimum width 1340 mm; Height 1951 mm; Ground Clearance 518 mm
Wheel set Rear 320/70R24 Front 240/70R16	Minimum width 1280 mm; Height 1981 mm; Ground Clearance 555 mm